

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problems Mailbox.**

This Page Blank (uspto)

(12) UK Patent Application (19) GB (11) 2 356 956 (13) A

(43) Date of A Publication 06.06.2001

(21) Application No 0029397.7

(22) Date of Filing 01.12.2000

(30) Priority Data

(31) 11342055 (32) 01.12.1999 (33) JP

(71) Applicant(s)

NEC Corporation
(Incorporated in Japan)
7-1 Shiba 5-chome, Minato-ku, Tokyo 108-01, Japan

(72) Inventor(s)

Shinichiro Iwata

(74) Agent and/or Address for Service

Mathys & Squire
100 Grays Inn Road, LONDON, WC1X 8AL,
United Kingdom

(51) INT CL⁷

G08B 5/22 7/06 , G09G 5/36

(52) UK CL (Edition S)

G4H HDC HRBS HRCU H1A H13D H14A H14B H14G
H60
U1S S2124 S2215

(56) Documents Cited

EP 0817143 A1 EP 0686949 A1 WO 97/19429 A1
WO 96/11454 A1 JP 090289553 A US 5828313 A

(58) Field of Search

UK CL (Edition S) G4H HRCU
INT CL⁷ G08B
ONLINE:WPI,EPODOC,JAPIO

(54) Abstract Title

E-mail character string conversion

(57) An electronic mail terminal includes a display section (23), a conversion dictionary (29) which stores sets of a character string and a pictograph, a receiving section and a control section which uses the dictionary to convert character strings in received electronic mail to pictographs where possible, to produce a pictograph mixed sentence, and controls the display section to display the pictograph mixed sentence. When requested, the meaning of a user-selected pictograph in the displayed sentence can also be displayed.

Fig. 2





Fig. 8B



GB 2 356 956 A

Fig. 1




Fig. 2




Fig. 4




Fig. 5




Fig. 6




Fig. 7A

今日は 天気 が 晴れ だ った の で 自転車 に 乗って 公園 へ 行きました。
(I WENT TO A PARK ON A BICYCLE SINCE IT WAS FINE TODAY.)




Fig. 7B

今日	SEP	-
天気	SEP	-
晴れ	SEP	☀
自転車	SEP	🚲
乗って	SEP	-
公園	SEP	🌳
行き	SEP	-

WORD LIST

Fig. 7C

今日は 天気 が 晴れ だったので 自転車 に 乗って 公園 へ 行きました。
(I WENT TO A PARK ON A BICYCLE SINCE IT WAS FINE TODAY.)

Fig. 8A




Fig. 8B




Fig. 9





Fig. 10



E-MAIL TERMINAL AUTOMATICALLY CONVERTING CHARACTER
STRING OF RECEPTION E-MAIL, AND E-MAIL SYSTEM

Background of the Invention

5 1. Field of the Invention

The present invention relates to an electronic mail terminal with a character string converting function and an electronic mail system.

2. Description of the Related Art

10 In recent years, a portable phone terminal has been provided for a data transmission function in addition to a telephone function. The transmission and reception of an electronic mail is possible between such portable phone terminals by use of the data
15 transmission function of the portable phone terminal. For this reason, in the portable phone terminal, it is generally made possible to input not only alphanumeric characters but also Japanese characters including Kanji characters. In this way, an advanced function
20 is requested for character input and character display, while the portable phone terminal is requested to have a small size and a light weight. Therefore, it is an important key to create a sentence efficiently with few keys and also to display the sentence efficiently
25 in a small display space.

Conventionally, a method of using a pictograph called an icon has been generally used in

such a situation. For example, a pictograph associated with a bicycle is used when the character string of "bicycle" is to be inputted. This allows the creation of a sentence to be made easy without
5 change the intention of the sentence, so that a display area can be saved. Such a technique is disclosed in Japanese Laid Open Patent Application (JP-A-Heisei 6-96056) as a first conventional example which describes a sentence creating technique using a
10 pictograph. In the first conventional example, it is supposed that the Japanese sentence of "はれならてにすをしよう" ("Harenara tenisuwo siyou"; "Let's play tennis, if whether is fine" in English) is inputted by a user and a pictograph conversion is instructed. In this
15 case, morpheme analysis is carried out to divide the Japanese sentence into the character strings of "はれ (hare)", "なら (nara)", "てにす (tenisu)", "を (wo)", and "しよう (siyou)". Then, a pictograph dictionary is used which stores a correspondence relation between
20 phonetic expression and the pictograph of the Japanese character string. The pictograph dictionary is searched based on the character strings to retrieve pictographs corresponding to the character strings of "hare" and "tenisu". In this case, if there are a
25 plurality of pictograph candidates for a single Japanese character string, the pictograph candidates are displayed for the user. The user selects one of

the displayed pictograph candidates.

In this way, an electronic mail system between the portable phone terminals has been conventionally constructed. However, in recent years, it has become possible to connect the portable phone terminal to the Internet based on the standard of WAP (Wireless Application Protocol), so that an electronic mail which is sent on the Internet can be directly received by the portable phone terminal.

However, in the access to the Internet electronic mail by the portable phone terminal, there are the following problems.

As the first problem, visibility is not good when the Internet electronic mail is displayed. As mentioned above, the pictographs are used in the conventional electronic mail transmission and reception between the portable phone terminals. However, no countermeasure is generally taken in the Internet electronic mail. That is, the electronic mail including pictographs cannot be sent. Therefore, when a long Internet electronic mail is displayed on a small display area of the portable phone terminal, a screen switching operation is required to switch the screens.

As the second problem, the whole sentence of an electronic mail sometimes can not be received when the long Internet electronic mail is received by the

portable phone terminal. The reason is that the maximum electronic mail length is determined in the portable phone terminal electronic mail system, and a part of the electronic mail exceeding the maximum
5 electronic mail length is not possible to be received by the portable phone terminal.

In conjunction with the above description, a communications system and a digital communication terminal are disclosed in Japanese Laid Open Patent
10 Application (JP-A-Heisei 10-98544). In this reference, a control unit (22) adds an originator number or various messages, which are inputted from a key input section (21) to a sub-address data which should be transmitted to a terminal on the side of reception on
15 originating call. Also, the control unit (22) adds a code to the head of the data to identify a classification of the data. Next, a transmitting and receiving section (10) and a communication control section (11) transmit the above sub-address data to
20 the terminal on the side of reception on the originating call. On the other hand, in call arrival, a reception sub address recognizing section (15) receives the sub-address data, which is transmitted from the terminal on the side of transmission. The
25 control unit (22) starts up a free character converting section (16), a fixed form sentence converting section (17), a pictograph converting

section (18), and an originator number converting
section (19) based on the code added to the sub-
address data, and decodes the received data. The
decoded data such as the originator number and the
5 various messages are displayed on a display section.
In this way, a message notice function and an
originator number notice function can be realized
between the different kinds of communications systems.

Also, an image processing apparatus is
10 disclosed in Japanese Laid Open Patent Application
(JP-A-Heisei 9-325958). In this reference, a
character string before conversion is displayed in a
display area (905) of a conversion screen, and a
character string after the conversion is displayed in
15 a display area (906). These character strings are
displayed in units of rows character by character. A
character string of "もじをへんかんする" is specified and
a pictograph converting button (1202) is clicked. At
that time, pictographs corresponding to the string are
20 carried to arrangement positions of the pictographs by
a hamster CH1. The pictograph CH2 corresponding to
the character string of "へん" before the conversion is
carried out above of the character of "へ". Then, the
character of "ん" is deleted from the screen.

Summary of the Invention

Therefore, an object of the preferred embodiments of the present invention is to provide an electronic mail terminal, in which a character string such as a word of a sentence of an electronic mail can be automatically converted
5 into a pictograph.

Another object of the preferred embodiments of the present invention is to provide an electronic mail terminal, in which a character string of a sentence of a transmission electronic mail can be automatically converted into a
10 pictograph, even if the transmission electronic mail is created without using any pictographs.

Still another object of the preferred embodiments of the present invention is to provide an electronic mail terminal, in which a character string of a sentence of a reception electronic mail can be automatically converted into
15 a pictograph.

Yet still another object of the preferred embodiments of the present invention is to provide an electronic mail terminal, in which meaning of a pictograph can be displayed, when a character string of a sentence of an electronic mail
20 can be converted into the pictograph.

It is also an object of the preferred embodiments of the present invention to provide an electronic mail system, in which a character string of a sentence of a transmission electronic mail can be automatically converted into a
25 pictograph, even if the transmission electronic

mail is created without using any pictographs.

In order to achieve an aspect of the present invention, an electronic mail terminal includes a display section, a conversion dictionary which stores
5 sets of a character string and a pictograph, a receiving section and a control section. The conversion dictionary stores sets of a character string and a pictograph. The receiving section receives an electric mail including a sentence as a
10 conversion object sentence in a reception mode. The control section automatically refers to the conversion dictionary based on each of character strings of the conversion object sentence in the reception mode to retrieve a specific pictograph corresponding to the
15 character string, when the pictograph corresponding to the character string is registered in the conversion dictionary. Then, the control section converts the character string into the specific pictograph to produce a pictograph mixed sentence, and controls the
20 display section to display the pictograph mixed sentence.

Here, one of the pictographs of the displayed pictograph mixed sentence may be specified. At this time, the control section may refer to the conversion
25 dictionary based on the specified pictograph in the reception mode to retrieve the character string corresponding to the specified pictograph, and control

the display section to display the retrieved character string. In this case, the control section may control the display section to display the pictograph mixed sentence and the retrieved character string at a same
5 time.

Also, the electronic mail terminal may further include an input section used to input a sentence in a transmission mode. At this time, the control section may refer to the conversion dictionary
10 based on a specified one of character strings of the inputted sentence in the transmission mode to retrieve a specific pictograph corresponding to the specified character string, when the pictograph corresponding to the specified character string is registered in the
15 conversion dictionary. Then, the control section converts the specified character string into the specific pictograph to produce a pictograph mixed inputted sentence, and controls the display section to display the pictograph mixed inputted sentence. In
20 this case, the electronic mail terminal may further include a transmitting section which transmits a transmission electronic mail in the transmission mode in response to a transmit instruction. The control section regards the pictograph mixed inputted sentence
25 as the transmission electric mail and issues the transmit instruction.

Also, when the inputted sentence is a Kana

sentence, and the conversion dictionary stores sets of
a Kana character string and a Kanji character string,
the control section refers to the conversion
dictionary based on each of specified ones of Kana
5 character strings of the inputted sentence in the
transmission mode to convert the specified character
string into Kanji characters to produce a Kanji
converted sentence, and regards the Kanji converted
sentence as the inputted sentence.

10 In another aspect of the present invention, a
method of displaying an electronic mail is attained
by receiving an electric mail including a sentence as
a conversion object sentence in a reception mode; by
automatically converting each of character strings into a
15 pictograph in the reception mode to produce a
pictograph mixed sentence when the pictograph
corresponding to the character string is defined; and
by displaying the pictograph mixed sentence.

In this case, the method may further include:
20 specifying one of the pictographs of the displayed
pictograph mixed sentence; determining a specific
character string corresponding to the specified
pictograph; and displaying the specific character
string. In this case, the pictograph mixed sentence
25 and the specific character string may be displayed at
a same time.

Also, the method may further include:

inputting a sentence in a transmission mode;
converting a specified one of character strings of the
inputted sentence to a specific pictograph corresponding
to the specified character string, to produce a
5 pictograph mixed inputted sentence; and displaying the
pictograph mixed inputted sentence.

Also, the method may further include:
transmitting the pictograph mixed inputted sentence in
the transmission mode.

10 Also, the method may be attained by
converting each of specified ones of Kana character
strings of the inputted sentence into Kanji characters
in the transmission mode, when the inputted sentence
is a Kana sentence,

15 In order to achieve still another aspect of the
preferred embodiments of the present invention, an electronic
mail relaying apparatus include a conversion dictionary, a
receiving section, a transmitting section and a control
section. The conversion dictionary stores sets of a character
20 string and a pictograph. The receiving section receives a
reception electronic mail including a sentence. The control
section automatically refers to the conversion dictionary
based on each of character strings of the sentence of the
reception electronic mail to retrieve a specific pictograph
corresponding to the character string, when the pictograph
25 corresponding to the character string is registered in the
conversion

dictionary. Then the control section converts the character string into the specific pictograph to produce the transmission electronic mail, and controls the transmitting section to transmit the transmission
5 electronic mail.

In order to achieve yet still another aspect of the present invention, an electronic mail apparatus includes a conversion dictionary, an input section and a control section. The conversion dictionary stores
10 sets of codes of a first expression format and codes of a second expression format, a code length of the first expression format codes being longer than that of the second expression format codes. The input section inputs an electronic mail including a first
15 sentence composed of sequences of the first expression format codes. The control section automatically refers to the conversion dictionary based on each of the sequences of the first expression format codes of the first sentence to retrieve a specific sequence of
20 the second expression format codes, and converts the sequence of the first expression format codes into the specific sequence of the second expression format codes to produce a converted sentence.

Also, the electronic mail apparatus may
25 further include an output section. In this case, the control section controls the output section to output an electronic mail including the converted sentence.

Also, when the input section inputs an electronic mail including a second sentence composed of the sequences of first expression format codes and the sequences of second expression format codes, the control section automatically refers to the conversion dictionary based on each of the sequences of second expression format codes of the second sentence to retrieve a specific sequence of the first expression format codes, and converts the sequence of the second expression format codes into the specific sequence of first expression format codes to produce an original sentence. Also, when the electronic mail apparatus further includes a display section, the control section may control the display section to display the original sentence.

Brief Description of the Drawings

Preferred features of the present invention will now be described, by way of example only, with reference to the accompanying drawings, in which:-

Fig. 1 is a block diagram showing the hardware structure of an electronic mail terminal according to the first embodiment of the present invention;

Fig. 2 is a functional block diagram showing the electronic mail terminal according to the first embodiment of the present invention;

Figs. 3A and 3B are diagrams showing an example of font data and an inner structure example of a display section;

Fig. 4 is a diagram showing a structure example of a Kana-Kanji conversion dictionary;

Fig. 5 is a flow chart showing an operation example at a Kanji-Pictograph converting section;

5 Fig. 6 is a flow chart showing a reception electronic mail displaying operation example of the electronic mail control section;

Figs. 7A to 7C are diagrams showing a specific example of the operation of the Kanji-
10 Pictograph converting section;

Figs. 8A and 8B are diagrams showing an example of a display screen of a reception electronic mail;

Fig. 9 is a block diagram of the second
15 embodiment of the present invention; and

Fig. 10 is a block diagram showing an example of a pictograph converting mechanism provided for a mail server.

20

Description of the Preferred Embodiments

Next, an electronic mail terminal of the present invention will be described below in detail with reference to the attached drawings.

25 Fig. 1 is a block diagram showing the structure of a portable phone terminal with the electronic mail function as the electronic mail

terminal according to the first embodiment of the present invention. Referring to Fig. 1, the portable phone terminal with the electronic mail function is composed of, as the hardware structure, a CPU 1, a ROM 2 connected with a bus 14, a RAM 3 used as a work area, a radio control section 4, an LCD controller 6, a key matrix control section 8, a speech input section 11, a speech output section 13, a radio section 5 connected with a radio control section 4, an LCD 7 connected with an LCD controller 6, numeric keys 9 connected with a key matrix control section 8, a microphone 10 connected with the speech input section 11, and a speaker 12 connected with the speech output section 13.

Various programs to operate the portable phone terminal, a Kana-Kanji conversion dictionary and a font data table are stored in the ROM 2. The CPU 1 controls each of the sections of the portable phone terminal in accordance with the programs stored in the ROM 2 to allow the terminal to function as the portable phone terminal with the electronic mail function. The functional block of the portable phone terminal realized by the hardware and the software is shown in Fig. 2.

Referring to Fig. 2, the portable phone terminal with the electronic mail function in this embodiment is composed of, as a functional blocks, an input section 21, a speech input/output section 22, a

display section 23, a communication section 24, a telephone control section 25, an electronic mail control section 26, a Kana-Kanji converting section 27, a Kanji-Pictograph converting section 28 and a character string-pictograph conversion table 33. It should be noted that 29 denotes a Kana-Kanji conversion dictionary stored in the ROM 2.

The input section 21 is a functional block, which is realized by the key matrix control section 8, the numeric keys 9 and the programs. In the input section 21, the key operated on the numeric keys 9 is detected by the key matrix control section 8 and the detected key operation is notified to the CPU 1 in the form of an interrupt signal. The input section 21 is used to input various instructions and data by the user. A switching operation of whether the portable phone terminal is used as a portable phone or as an electronic mail terminal can be selected, and a dial number and a call originating instruction can be inputted when the portable phone terminal is used as the portable phone terminal. Also, transmission and reception instructions and a mail address and electronic mail sentences are inputted when the portable phone terminal is used as the electronic mail apparatus.

The speech input/output section 22 is a functional block which is realized by the microphone

10, the speech input section 11, the speaker 12, and the speech output section 13, and is mainly used at the time of the portable phone terminal. The speech input section 11 contains an amplifier, which
5 amplifies an inputted speech signal from the microphone 10, and an analog-to-digital converter, which converts the amplified speech signal into a digital signal. The speech output section 13 contains a digital-to-analog converter, which converts a
10 digital speech signal outputted from the CPU 1 into an analog signal, and an amplifier, which amplifies the analog signal.

The communication section 24 is a functional block, which is realized by the radio control section
15 4, the radio section 5 and the programs, and is used at the time of communication with another telephone using a portable phone network, and at the time of the Internet connection. The radio control section 4 carries out the control of communications protocols,
20 and the radio section 5 contains a modulator, demodulator and a transmission and reception antenna.

The display section 23 is a functional block which is realized by the LCD controller 6, the LCD 7, a font data table (not shown) stored in the ROM 2 and
25 the programs, and is used for the display of the dial number in the use as the portable phone and the display of a reception electronic mail in the use as

the electronic mail terminal. An example of the font data and the internal structure example of the display section 23 are shown in Figs. 3A and 3B.

The LCD controller 6 basically has only the function to control the LCD 7 to display a dot on a specified position. Therefore, font data as shown in Fig. 3A is used to display a character. The font data is prepared as a bit pattern in which a display required dot is "1" and a display not-required dot is "0" when a character is expressed in a square lattice as shown in Fig. 3A. The font data is a display bit pattern of the character itself so that an amount of data is large. Also, the font data to the same character are different depending on the structure of the display section. Thus, the compatibility between the font data is low. Therefore, the character is managed in the form of a character code, when the character is manipulated in a case other than the display.

For example, as shown in Fig. 3A, the character code of "IWA" (rock in English) is predetermined to be "8AE2". Thus, the character code of "8AE2" can be recognized as the character of "IWA" in any apparatuses. In case of the display of the character on the display section 23, a display requesting source designates the character code and the display position data to output to the font data

converting section 31. The font data converting section 31 is realized by the program, which is stored in the ROM 2. The font data converting section 31 refers to the font data table based on the character
5 code to read out corresponding font data and display position data, and outputs a display request with the font data and the display position data to the LCD controller 6. The LCD controller 6 controls the LCD 7 in accordance with the display request to display the
10 character pattern of "IWA" on the LCD 7. Like the character of "IWA", various pictographs are managed by use of the character codes and the font data.

The telephone control section 25 is a functional block, which is realized by the program,
15 and is connected with the input section 21, the speech input/output section 22, the display section 23 and the communication section 24. The telephone control section 25 carries out the controls of general functions of the portable phone such as the
20 transmission control and the reception control.

The electronic mail control section 26 is a functional block, which is realized by the program, and is connected with the input section 21, the display section 23, the communication section 24, the
25 Kana-Kanji converting section 27 and the Kanji-Pictograph converting section 28. The electronic mail control section 26 carries out the control of general

functions relating to the transmission and reception of an electronic mail.

The Kana-Kanji converting section 27 is a functional block, which is realized by the program.

5 The Kana-Kanji converting section 27 has a function to refer to the Kana-Kanji conversion dictionary 29 to convert Kana characters inputted from input section 21 into kanji characters. An example of the Kana-Kanji conversion dictionary 29 is shown in Fig. 4.

10 Referring to Fig. 4, the Kana-Kanji conversion dictionary 29 is mainly composed of two kinds of tables of a phonetic table 41 and a word table 42.

The phonetic table 41 stores a set of records
15 for a predetermined phonetic expression. One record corresponding to the phonetic expression is composed of a set of phonetic data 41-1 and a pointer (address) P1 to P5. The pointer points the address of a record corresponding to the phonetic expression in the word
20 table 42. A separator code (Sep) divides the phonetic data 41-1 and the pointer.

The word table 42 stores a set of records for every word. One record corresponding to a word is composed of a set of word data 42-1 and pictograph
25 data 42-2 corresponding to the word. A separator code (Sep) divides into the word data 42-1 and the pictograph data 42-1. The pictograph data 42-1 is

previously written with a code of the pictograph, when the pictograph corresponding to the word exists, and is written with a NULL value (shown by "-" in Fig. 4), when the corresponding pictograph does not exist.

5 For example, it is supposed that the Kana character string of "kouen" is inputted from the user through the input section 21 and the Kana-Kanji conversion is instructed. The Kana-Kanji converting section 27 searches a phonetic table 41 for the
10 records having the phonetic expression of "kouen". Then, the word table is searched based on the first pointer so that the Kanji character string of "公園" ("kouen"; "park" in English) is determined as a candidate. Thus, the Kanji character string of "公園"
15 is displayed on the display section 23 for the user. When this Kanji character string of "公園" is not the candidate which the user wants, the Kanji character string of "講演" ("kouen"; "lecture" in English) which is stored in the address pointed by the second pointer
20 P2 in response to the operation of the user operation is displayed as the next candidate. Hereinafter, similarly, "後援" ("kouen"; "support" in English), "公演" ("kouen"; "performance" in English), and "好演" ("kouen"; "good performance" in English) are
25 appropriately displayed, and the user can select a desired candidate.

Also, it is supposed that the phonetic

expression of "kouen" is inputted from the user through the input section 21 and the Kana-pictograph conversion is instructed. In this case, the records having the phonetic expression of "kouen" are searched
5 from the phonetic table 41. Then, the pictograph of "公園" ("kouen"; "park" in English) stored in the record of the word table 42 which is pointed by the first pointer P1 of one of the searched records is displayed on the display section as a candidate for
10 the user. When this candidate is not the candidate which the user wants, the next candidate is displayed, as in the Kana-Kanji conversion. However, in case of Fig. 4, only the pictograph of "公園" is stored in the word table 42 as the pictograph corresponding to the
15 phonetic expression of "kouen". Therefore, the display of the next candidate is not carried out. It should be noted that a plurality of pictographs corresponding to the single phonetic expression might be displayed at a time so that the user can select
20 one of the plurality of pictographs.

By using the Kana-Kanji converting section 27 having the above mentioned function, the user creates an electronic mail sentence including the Kanji character strings and an electronic mail sentence
25 including pictographs and can transmit the electronic mail to another portable terminal through the electronic mail control section 26.

On the other hand, the Kanji-Pictograph converting section 28 receives the sentence of the received electronic mail from the electronic mail control section 26. Then, the Kanji-Pictograph
5 converting section 28 refers to the Kana-Kanji conversion dictionary 29 based on the word (character string) of the electronic mail sentence, automatically substitutes a pictograph for the word and sends the substituted sentence back to the electronic mail
10 control section 26. The above-mentioned Kana-Kanji converting section 27 converts "phonetic expression" into the pictograph but the Kanji-Pictograph converting section 28 converts the word in the electronic mail sentence into the pictograph directly
15 without converting the word into the phonetic expression. More specifically, the word table 42 of Fig. 4 is searched using the word to be substituted of the electronic mail sentence as a key to retrieve the pictograph. An example of the processing is shown in
20 Fig. 5. It should be noted that it is presupposed that an EOF (End Of File) code is stored as the last character of the electronic mail transferred from the electronic mail control section 26. In other words, the EOF code is stored as the eleventh character if
25 the sentence is composed of the total number of characters of "10".

Referring to Fig. 5, at first, a variable i

indicative of a character position is initialized to "1" and a variable j indicative of a word character length is initialized to "0" (steps S1 and S2).

Subsequently, a determination is carried out to see
5 whether or not the word starting with the character which exists on the character position i is registered on the word table 42 (step S3). When the word is not registered, the character, i.e., the character at the character position i is outputted just as it is. Also,
10 the character position variable i is incremented by one (step S10). Then, when the next character is not the last character EOF (step S9), the control flow returns to the initial procedure.

When the word starting with the character on
15 the character position i is registered on the word table 42, the word length j is incremented by one (step S4). Then, a determination is carried out to see whether the word composed of characters on the character positions i to i+j is registered on the word
20 table 42 (step S5). For example, when the fourth character is "天" ("ten"; "sky" or "heaven" in English) and the fifth character is "気" ("ki"; "feeling" or "look" in English), and i is four and j is one, it is determined whether or not the word of
25 "天気" ("tenki"; "weather" in English) is registered on the word table 42. When the word of "天気" is not registered, the characters on the character positions

i to i+j-1 are outputted just as it is. Also, the character variable is set to the character position of i+j (step S11). If the next character is not the last character EOF (step S9), the control flow returns to
5 the first procedure. In other words, the characters of the word determined at the step S5 other than the last character are outputted and the same procedure is started from the last character once again.

Next, it is determined whether or not the
10 above-mentioned word is unique in the word table 42 (step S6). This means to determine whether or not a word composed of the word of "天気" in the above-mentioned example and characters following the word of "天気" is registered on the word table 42. Only, if
15 the word is not unique, the control flow returns to the step S4, and the word length variable j is incremented by one to repeat the same procedure once again.

When the above-mentioned word is unique in
20 the word table 42, it is determined whether or not the word has a pictograph in the word table 42 (step S7). When the word has the pictograph, the pictograph is outputted together with the character positions i and i+j (step S8). The character positions are outputted.
25 When the word does not have the pictograph, the word is outputted just as it is (step S12). When setting the character position variable is set to i+j+1 in

either case (steps S8 and S12). When the next character is not the last character EOF (step S9), the control flow returns to the initial procedure. In other words, the same procedure is repeated once again
5 from the character next to the outputted word.

When the character of character position 1 is determined to be the EOF code in the step S9, the processing is ended at the point.

Next, the operation of the portable phone
10 terminal with the electronic mail function in this embodiment having the above mentioned structure will be described. It should be noted that the operation when the portable phone terminal is used as the portable phone, and the operation when the portable
15 phone terminal is used as the electronic mail apparatus are same as those of the conventional portable phone terminal with the electronic mail function. Therefore, a displaying operation of a reception electronic mail which is one feature of this
20 embodiment will be described in detail.

For example, it is supposed that the Internet electronic mail is received by the communication section 24 through a portable phone network in response to an operation of the input section 21 by
25 the user. In this case, the electronic mail control section 26 starts a reception electronic mail displaying process as shown in Fig. 6. First, the

electronic mail sentence of the reception electronic mail is transferred to the Kanji-Pictograph converting section 28 to substitute pictographs for words in the electronic mail sentence (step S21). The operation of
5 the Kanji-Pictograph converting section 28 in this case is already described with reference to Fig. 5. Then, the substituted electronic mail sentences and the position data of the word before the substitution for every pictograph are returned to the electronic
10 mail control section 26. The electronic mail control section 26 transfers the returned electronic mail sentences and the returned display positions to the display section 23 such that the returned electronic mail sentences are displayed on a predetermined area
15 of the LCD 7 (step S22).

After that, every time the pictograph in the displayed electronic mail sentences is pointed from the user by a pointing means such as a cursor (step S23), the electronic mail control section 26 supplies
20 the word before the substitution corresponding to the pointed pictograph and the display positions of the word to display section 23 such that the electronic mail sentences including the word is displayed in another area of the LCD 7 (step S24). Then, when a
25 display end instruction is supplied from the input section 21 (step S25), the process of Fig. 6 is ended. It should be noted that the word before the

substitution corresponding to the pictograph is the word of the electronic mail sentences before the substitution which is specified by the character position data which is returned from the Kanji-

5 Pictograph converting section 28 at the step S8 of Fig. 5 together with the pictograph.

Hereinafter, a specific example of the displaying method of reception electronic mail will be described.

10 For example, it is supposed that the electronic mail of "今日は天気が晴れだったので自転車に乗って公園へ行きました" (Kyouha haredattanode jitensyaninotte kouennhe ikimasita"; "I went to a park on a bicycle since it was fine today" in English) is received, as
15 shown in Fig. 7A. When the reception electronic mail is transferred from the electronic mail control section 26, the Kanji-Pictograph converting section 28 refers to the word table 42 to words in the electronic mail sentence into the pictographs. Fig. 7B shows a
20 list of words of the word table 42 which are coincident with the words of the electronic mail sentence. The word of "今日" ("kyou"; "today" in English) is unique in the word table 42 but the pictograph is not defined or registered. Therefore,
25 the word of "今日" is outputted just as it is. Subsequently, because the word of "は" ("wa") is not present in the word table 42, the word of "は" is

outputted just as it is. Similarly, the words of "天気" ("tenki") and "が" ("ga") are outputted just as they are for the same reason. The word of "晴れ" ("hare"; "fine" in English) is uniquely present in the word table 42, and a pictograph is defined. Therefore, the pictograph is outputted in place of the word of "晴れ". Hereinafter, by following the procedure of Fig. 5, three words of "晴れ", "自転車" ("jiten-sya"; "bicycle" in English), and "公園" ("kouen"; "park" in English) are converted into the pictographs, as shown in Fig. 7C.

The electronic mail control section 26 controls the display section to display the electronic mail sentence which is converted by the Kanji-Pictograph converting section 28, in a predetermined display area 71 of the LCD 7, as shown in Fig. 8A. At this point of time, a cursor 73 is located on not the pictograph but a character portion. Therefore, "meaning: " is only displayed in a display area 72 which is provided in a lower portion of the display area 71.

Next, when the cursor 73 is moved onto the pictograph which expresses the bicycle by the user as shown in Fig. 8B, the electronic mail control section 26 determines the word of "自転車" before the conversion based on the character position data and the reception electronic mail sentence which have been

outputted from the Kanji-Pictograph converting section 28 together with the pictograph of the bicycle. Then, the word of "自転車" is displayed in the display area 72, as shown in Fig. 8B. This operation allows the
5 user to easily recognize the meaning of the displayed pictograph, even if the user cannot recognize the meaning of the pictograph.

As mentioned above, the contents of an electronic mail is easy to understand when the
10 electronic mail is read even if a display area is narrow. The reason is that the words are converted into the pictographs in case of display of the electronic mail so that the characters in the whole sentence can be decreased. Therefore, more data can
15 be displayed in the narrow display area.

Also, the original sentence can be immediately referred to in case of pictograph display. The reason is that the original word before the conversion can be displayed when the user moves the
20 cursor to the position of the pictograph in the display state of the converted electronic mail.

Also, it is not necessary to newly prepare a correspondence table of the word and the pictograph. The reason is that the conversion or substitution is
25 realized by diverting the Kana-kanji conversion dictionary and by adding a pictograph to the word table.

It should be noted that in this embodiment, a word of the reception electronic mail sentence is always converted into a pictograph and displayed, when the pictograph corresponding to the word is registered.

5 However, a flag may be provided in the electronic mail control section 26 to switch an effective state and invalid state of the pictograph converting function. In this case, only when this flag is set by the user to make the pictograph converting function effective,
10 the word of the reception electronic mail sentence is automatically converted into the pictograph and displayed. Also, when the pictograph converting function is made invalid, the reception electronic mail sentence is displayed just as it is.

15 Also, as the word table, which stores the correspondence relation of the word and the pictograph, the Kana-Kanji conversion dictionary is used. However, the word table of exclusive use may be used. In this case, it is sufficient for only the words
20 corresponding to the existing pictographs to be present in the word table.

Also, the word before the substitution corresponding to the pictograph specified by the cursor is determined from the original electronic mail
25 sentence and the position data obtained in the converting process in the Kanji-Pictograph converting section 28. However, the record of the word table 42

is searched using the pictograph specified by the cursor as a key, to determine a word before the conversion.

Also, in this embodiment, the present
5 invention is applied to the portable phone terminal with the electronic mail function. However, the present invention is possible to widely apply to the apparatus which has an electronic mail function.

In addition, a sentence inputted from the
10 input section and composed of codes of a first expression format is subjected to the pictograph conversion to have codes of a second expression format. Then, the sentence including the pictographs is transmitted. On the reception end, the pictographs
15 may be automatically returned to the character codes of the first expression format. In this case, the mail length to be transmitted can be shortened.

In the first embodiment, the conversion from the word into the pictograph is carried out on the
20 side of the terminal. However, in the second embodiment, the conversion is carried out in a mail server 91, which is provided in a portable phone network 90, as shown in Fig. 9. An electronic mail destined to a portable phone terminal 92 with the
25 electronic mail function which is sent via the Internet 93 is accumulated in the mail server 91. The electronic mail which is stored in the mail server 91

is downloaded on the portable phone terminal 92 and is displayed. Therefore, if a word is converted into a pictograph in the mail server 91 before the download, the converting operation shown in the flow chart of Fig. 5 on the side of portable phone terminal 92 becomes unnecessary.

An example of the pictograph convert mechanism which is provided for the mail server 91 is shown in Fig. 10. A file apparatus 100 accumulates electronic mails destined to the portable phone terminal and sent via the Internet 93. A word table 101 is the table which stores correspondence relation of the word and the pictograph. A Kanji-Pictograph converting section 102 refers to the word table 101 to automatically convert words in the electronic mail sentence which is accumulated in the file apparatus 100 into the pictographs, in the same method as that of the Kanji-Pictograph converting section 28 of Fig. 2. The conversion may be carried out each time a new electronic mail is stored in the file apparatus 100. Instead, the conversion may be carried out to the electronic mail to be downloaded immediately before the portable phone terminal 92 downloads the electronic mail.

It should be noted that the existing portable phone 92 can be used just as it is as the portable phone terminal with the electronic mail function.

However, the word table like the word table 101 may be provided. Also, a function may be provided to search the word table based on the pictograph specified by a cursor from the user to retrieve the word

5 corresponding to the specified pictograph and to display the retrieved word on a display area 72, as shown in Fig. 8. In this case, the user can recognize the meaning of the displayed pictograph.

According to the second embodiment, the
10 following effect is attained in addition to the effect in the first embodiment.

First, the first effect is in that it is possible to reduce the possibility that the whole text of the electronic mail is not displayed. In the
15 portable phone electronic mail system often defines the maximum electronic mail length and the part of the electronic mail exceeding the maximum electronic mail length cannot be received on the side of the portable phone terminal. However, according to the present
20 invention, the possibility to be against the limitation becomes low by previously converting words into pictographs on the side of the mail server so that the number of the characters in the sentence can be reduced.

25 The second effect is in that the resource load and the processing load on the side of the portable phone terminal can be reduced. It is not

necessary to incorporate pictographs into the word table. Also, the converting operation shown in the flow chart of Fig. 5 is not necessary in case of electronic mail display.

5 The present invention is described using the embodiments. However, the present invention is not limited only to above embodiments and various types of additional modifications are possible. For example, in each of the embodiments, a word is converted into
10 the pictograph. However, the present invention is not limited to the conversion of the word into the pictograph. In the present invention, an optional character string may be converted into a pictograph. The optional character string includes a word, an
15 idiom composed of plurality of words, a phrase, and a sentence. Also, the present invention may be applied to a terminal of the English notation. In case of English, it is necessary to newly provide a table storing correspondence relation of an English word and
20 a pictograph, because there is no system for Kana-Kanji conversion. In the case of English, the conversion from the word into the pictograph is easy because a word is separated from another word by a space.

25 As described above, the following effect is attained in accordance with the present invention.

 The contents of an electronic mail is easy to

understand when the electronic mail is read even if a display area is narrow. The reason is that the words are converted into the pictographs in case of display of the electronic mail so that the characters in the whole sentence can be decreased. Therefore, more data can be displayed in the narrow display area.

The original sentence can be immediately referred to in case of pictograph display. The reason is that the original word before the conversion can be displayed when the user moves the cursor to the position of the pictograph in the display state of the converted electronic mail.

It is not necessary to newly prepare a correspondence table of the word and the pictograph, by diverting the Kana-kanji conversion dictionary for adding a pictograph to the word table.

The first effect is in that it is possible to reduce the possibility that the whole text of the electronic mail is not displayed. The portable phone electronic mail system often defines the maximum electronic mail length and the part of the electronic mail exceeding the maximum electronic mail length cannot be received on the side of the portable phone terminal. However, according to the present invention, the possibility to be up against that limitation is reduced by previously converting words into pictographs on the side of the mail server so

that the number of the characters in the sentence can be reduced. Also, because the converting process to the word table and the pictograph on the terminal side becomes unnecessary, there is the effect that a resource load and a processing load can be reduced on the terminal side.

While the present invention has been described in its preferred embodiments, it is to be understood that the words which have been used are words of description rather than limitation, and that changes may be made to the invention without departing from its scope as defined by the appended claims.

Each feature disclosed in this specification (which term includes the claims) and/or shown in the drawings may be incorporated in the invention independently of other disclosed and/or illustrated features.

The text of the abstract filed herewith is repeated here as part of the specification.

An electronic mail terminal includes a display section, a conversion dictionary which stores sets of a character string and a pictograph, a receiving section and a control section. The conversion dictionary stores sets of a character string and a pictograph. The receiving section receives electronic mail including a sentence as a conversion object sentence in a reception mode. The control section automatically refers to the character string-pictograph conversion dictionary based on each of character strings of the conversion object sentence in the reception mode to retrieve a specific pictograph corresponding to the character

string, when the pictograph corresponding to the character string is registered in the character string-pictograph conversion dictionary. Then, the control section converts the character string into the specific pictograph to produce a
5 pictograph mixed sentence, and controls the display section to display the pictograph mixed sentence.

CLAIMS:

1. An electronic mail terminal for receiving electronic mails containing character strings, some of the character strings being converted into pictographs according to a stored dictionary containing sets of the character strings and corresponding pictographs, the received electronic mails being displayed after conversion by the dictionary as pictograph mixed sentences containing both character strings and pictographs.
2. An electronic mail terminal comprising:
 - a display section;
 - a conversion dictionary which stores sets of a character string and a pictograph;
 - a receiving section which receives an electronic mail including a sentence as a conversion object sentence in a reception mode;
 - a control section which automatically refers to said conversion dictionary based on each of character strings of said conversion object sentence in said reception mode to retrieve a specific pictograph corresponding to said character string, when said pictograph corresponding to said character string is registered in said conversion dictionary, converts said character string into said specific pictograph to produce a pictograph mixed sentence, and controls said display section to display said pictograph mixed sentence.
3. The electronic mail terminal according to claim 2, wherein when one of said pictographs of the displayed pictograph mixed sentence is specified, said control section refers to said conversion dictionary based on said specified pictograph in said reception mode to retrieve the character string corresponding to said specified pictograph, and controls said display section to display said retrieved character string.

4. The electronic mail terminal according to claim 3, wherein said control section controls said display section to display said pictograph mixed sentence and said retrieved character string at a same time.

5. The electronic mail terminal according to any of claims 2 to 4, further comprising:

an input section used to input a sentence in a transmission mode, and

5 wherein said control section refers to said conversion dictionary based on a specified one of character strings of said inputted sentence in said transmission mode to retrieve a specific pictograph corresponding to said specified character string, when
10 said pictograph corresponding to said specified character string is registered in said conversion dictionary, converts said specified character string into said specific pictograph to produce a pictograph mixed inputted sentence, and controls said display
15 section to display said pictograph mixed inputted sentence.

6. The electronic mail terminal according to claim 5, further comprising:

a transmitting section which transmits a

transmission electronic mail in said transmission mode
5 in response to a transmit instruction, and

wherein said control section regards said
pictograph mixed inputted sentence as said
transmission electronic mail and issues said transmit
instruction.

7. The electronic mail terminal according to claim
6, wherein said inputted sentence is a Kana sentence,
said conversion dictionary stores sets of a
Kana character string and a Kanji character string,
5 and

said control section refers to said conversion
dictionary based on each of specified ones of Kana
character strings of said inputted sentence in said
transmission mode to selectively convert said
10 specified character string into a Kanji character
string to produce a Kana-Kanji converted sentence, and
regards said Kana-Kanji converted sentence as said
inputted sentence.

8. A method of displaying electronic mail,
comprising:

receiving electronic mail including a sentence
as a conversion object sentence in a reception mode;
5 automatically converts each of character string
into a pictograph in said reception mode to produce a

pictograph mixed sentence when said pictograph corresponding to said character string is defined; and displaying said pictograph mixed sentence.

9. The method according to claim 8, further comprising:

specifying one of said pictographs of the displayed pictograph mixed sentence;

5 determining a specific character string corresponding to said specified pictograph; and displaying said specific character string.

10. The method according to claim 9, wherein said displaying includes:

displaying said pictograph mixed sentence and said specific character string at a same time.

11. The method according to claim 9 or 10, further comprising:

inputting a sentence in a transmission mode;

converting a specified one of character strings

5 of said inputted sentence a specific pictograph corresponding to said specified character string, to produce a pictograph mixed inputted sentence; and displaying said pictograph mixed inputted sentence.

12. The method according to claim 11, further comprising:

transmitting said pictograph mixed inputted sentence in said transmission mode.

13. The method according to claim 12, wherein said inputted sentence is a Kana sentence,

said method further comprises:

converting each of specified ones of Kana
5 character strings of said inputted sentence into Kanji characters in said transmission mode.

14. An electronic mail relaying apparatus comprising:

a conversion dictionary which stores sets of a character string and a pictograph;

5 a receiving section which receives a reception electric mail including a sentence;

a transmitting section; and

a control section which automatically refers to said conversion dictionary based on each of character
10 strings of said sentence of said reception electric mail to retrieve a specific pictograph corresponding to said character string, when said pictograph corresponding to said character string is registered in said conversion dictionary, converts said character
15 string into said specific pictograph to produce said

transmission electronic mail, and controls said transmitting section to transmit said transmission electronic mail.

15. An electronic mail apparatus comprising:

a conversion dictionary which stores sets of codes of a first expression format and codes of a second expression format, a code length of said first expression format codes being longer than that of said second expression format codes;

an input section which inputs an electric mail including a first sentence composed of sequences of said first expression format codes; and

10 a control section which automatically refers to said conversion dictionary based on each of said sequences of said first expression format codes of said first sentence to retrieve a specific sequence of said second expression format codes, and converts said sequence of said first expression format codes into said specific sequence of said second expression format codes to produce a converted sentence.

16. The electronic mail apparatus according to claim 15, further comprising:

an output section, and

wherein said control section controls said output section to output an electronic mail including

said converted sentence.

17. The electronic mail apparatus according to claim 16, wherein when said input section inputs an electric mail including a second sentence composed of said sequences of first expression format codes and
5 said sequences of second expression format codes, said control section automatically refers to said conversion dictionary based on each of said sequences of second expression format codes of said second sentence to retrieve a specific sequence of said first
10 expression format codes, and converts said sequence of said second expression format codes into said specific sequence of first expression format codes to produce an original sentence.

18. The electronic mail apparatus according to claim 17, further comprising a display section, and wherein said control section controls said display section to display said original sentence.

19. An electronic mail terminal substantially as herein described with reference to and as shown in the accompanying drawings.

20. A method of displaying electronic mail, the method

being substantially as herein described with reference to and as shown in the accompanying drawings.

21. An electronic mail relaying apparatus substantially as herein described with reference to and as shown in the accompanying drawings.



INVESTOR IN PEOPLE

Application No: GB 0029397.7
Claims searched: 1-13,19-20

Examiner: Mike Davis
Date of search: 20 February 2001

Patents Act 1977 Search Report under Section 17

Databases searched:

UK Patent Office collections, including GB, EP, WO & US patent specifications, in:

UK Cl (Ed.S): G4H (HRCU)

Int Cl (Ed.7): G08B

Other: Online: WPI, EPODOC, JAPIO

Documents considered to be relevant:

Category	Identity of document and relevant passage	Relevant to claims
X	EP 0817143 A1 (NEC)	1,2,8 at least
X	EP 0686949 A1 (CASIO COMPUTER)	"
X	WO 97/19429 A1 (MOTOROLA)	"
X	WO 96/11454 A1 (PHILIPS ELECTRONICS)	"
X	US 5828313 (MOCHIZUKI)	"
X	JP 090289553 A (YOSHIMI) and its WPI abstract (Accession No. 1998-030517 [03]) and JAPIO(=PAJ) abstract	"

X	Document indicating lack of novelty or inventive step	A	Document indicating technological background and/or state of the art.
Y	Document indicating lack of inventive step if combined with one or more other documents of same category.	P	Document published on or after the declared priority date but before the filing date of this invention.
&	Member of the same patent family	E	Patent document published on or after, but with priority date earlier than, the filing date of this application.

This Page Blank (uspto)